



Saves Your Energy

PRODUCT CARD

22.4.2016

KS3.25

Name:	3-pole switch 3 x 25 A, with direct handle, panel and DIN rail mounted
Type:	KS3.25
GTIN:	6418677170003
Description:	Ensto Compact is a complete range of rotary switches from 16 A to 125 A.
Package:	1/50
Unit:	PCS



Photo presented is indicative only



Technical specification

Electrical values

Breaking capacity 415 V, AC 23 A	200 A
Making capacity 415 V, AC 23 A	250 A
Rated insulation voltage	800 V
Rated operational current	AC 22 A: 415V / 25A, 500V / 25A, 690V / 25A, AC 23 A: 415V / 25A, 500V / 25A, 690V / 25A

Short-circuit characteristics

Max. cut-off current	6 kA
Max. fuse	25 A
Max. Joule integral	6.8
Rated conditional short-circuit current	50 nA
Rated short time withstand current	1260 A (1 s)

Ratings

ETIM class	Switch disconnecter
Rated impulse withstand voltage	8 kV

Mechanical

Tightening torque	2 Nm
-------------------	------

Dimensions

Weight	0.13 kg
Volume	26.86 cm ³
Conductor cross-section	Cu 1.5-16
Size	40 x 85 x 79

Certificates

Standards	EN 60947-3
-----------	------------

Ensto Finland Oy

Ensio Miettisen katu 2
P.O.Box 77
06101 Porvoo, Finland

Tel. +358 204 76 21
Fax +358 204 76 2516

www.ensto.com